



# Piranha

## Submersible Dewatering Pumps

### Model P-1500

**15 HP / 4 & 6 Inch Discharge**  
**230v/460v/575v three phase**

Home Of Piranha Pumps [www.piranhapump.com](http://www.piranhapump.com)

#### *Pump Construction*

- Housing 356T6 Al Alloy
- Mechanical Seals Silicon Carbide
- Impeller Heat Treated 17-4 PH SS
- Rotor Shaft 416 SS
- Lower Diffuser Nitrile Rubber – Adjustable
- Discharge Lining Nitrile Rubber
- Strainer 316 SS 3/8"x1 1/4" Openings
- Hardware 304 SS
- Pump Weight 220 Lbs
- Lifting Handle 316 SS With Rubber Grip



#### *Motor Specifications*

- Motor Seal Double Oring
- Rating 3 Phase 15 HP
- Voltage 230 / 460 Volt
- Current F.L.A. 40 / 20
- Thermal Overload 2 Integral Switches
- Circuit Breaker Short Circuit, Locked Rotor, & Overload Protection
- RPM 3450
- Insulation Class F / 310 Degrees F
- Power Cable 50' 6/3 SOW-A
- Control NEMA 4X

**Piranha Model P-1500 HV & HH**  
 15 HP - 230 / 460 Volt

